


REMARKS

The present amendment corrects a number of typographical errors which were noted in the specification after filing. In view of the relatively large number of such changes, it is easier to submit a Substitute Specification embodying all of those changes, rather than making a paragraph-by-paragraph amendment.

A typographical error in claim 1 also has been corrected. Claims 8 and 18 have been editorially revised to employ language consistent with the specification. None of the amendments to claims 1, 8 and 16 has been made for a reason substantially relating to patentability, nor are any of those amendments narrowing amendments.

Early consideration on the merits is respectfully requested.

Submitted by,



(Reg. 28,982)

SCHIFF, HARDIN & WAITE
Patent Department
6600 Sears Tower
233 South Wacker Drive
Chicago, Illinois 60606
Telephone: 312/258-5790
Attorneys for Applicants
CUSTOMER NO. 26574

VERSION WITH MARKINGS TO SHOW CHANGES MADE

1. (Amended) A data transmission system comprising:

a stationary part;

a rotary part rotatable relative to said stationary part;

a source of gigabit/sec data at said rotary part, said data being subject to jitter;

a slip ring system for transmitting said data from said rotary part to said stationary part, said slip ring system having a rotary slip ring module at said rotary part and a stationary slip ring module at said stationary part;

a first gigabit/sec data link proceeding from said source at said rotary part;

a first clock regenerator connected to said first data link at said rotary [~~slipping~~]
slip ring module;

a receiver for said gigabit/sec data at said stationary part;

a second gigabit/sec data link proceeding to said receiver at said stationary part;
and

a second clock regenerator connected to said second data link at said stationary slip ring module, said first and second clock regenerators synchronizing said gigabit/sec data, proceeding from said first data link and proceeding to said second data link, to a stable reference clock to prevent said jitter from proceeding from said source to said receiver.

Claim 8 has been amended as follows:

8. (Amended) A data transmission system as claimed in claim 7 wherein each of said parallel clock regenerators calculates [~~cycling~~] a cyclic redundancy check code for each of said packets, and wherein said parallel clock regenerator at said rotary part transmits said [~~cycling~~] cyclic redundancy check code to said source for [~~minimizing~~]

jitter] use in detecting transmission errors in said first data link and wherein said parallel clock regenerator at said stationary part transmits said [cycling] cyclic redundancy check code to said receiver for [eliminating jitter] use in detecting transmission errors in said second data link.

Claim 18 has been amended as follows:

18. A method as claimed in claim 17 comprising, at each of said first and second parallel clock regenerators, calculating a [cycling] cyclic redundancy check code for each of said packets, and transmitting the [cycling] cyclic redundancy check code calculated at said first parallel clock regenerator to said source for [minimizing jitter] use in detecting transmission errors in said first data link, and transmitting said [cycling] cyclic redundancy check code from said second parallel clock regenerator to said receiver for [eliminating jitter] use in detecting transmission errors in said second data link.

CHI_DOCS2:CS2511752.1 07.15.01 11.43